

## Dual-Row



### Two Rows per Tracker

Agile™-1P is a dual-row tracker with one primary slewing drive in one row and one secondary slewing drive in another row. Two slewing drives share one motor and one TCU.



### Innovative SuperTrack Technology

According to real-time weather and actual terrain conditions, smart algorithm dynamically optimizes tracking angle, increases receiving radiation and reduces shading loss.

Up to 8% yield gain



### More Modules per Tracker

Compatible with modules up to 670W+



### Designed for Challenging Conditions

The Agile™-1P has been designed for sites that have both challenging terrain and high wind conditions

Up to 20% N-S slope.




### Higher Reliability

The two slewing drives in Agile™-1P are connected by a transmission bar with a cardan design that improves the transmission efficiency, also has an optimized stow position and alarm strategy for a safer and more robust structure.

### TRINA CLAMP

Trina Clamp is a proprietary product that is quick and easy to use with the 1P configuration, reducing the installation time and costs.



### WIND TUNNEL TESTED BY CPP

Detailed wind tunnel test methodology to reproduce the most realistic tracker behavior and analyze the aerodynamic effects that impact tracker structures.

# TECHNICAL SPECIFICATIONS

## GENERAL FEATURES

Solar tracker type	Horizontal Single-Axis with two rows
Tracking range	$\pm 60^\circ$ (120°)
Driver	Cardan joined slewing drive
	One module in portrait (1P) up to 2 string
Solar module supported	Framed
Foundation options	Direct ramming, Pre-drilling + ramming, M
Pile section	W, compatible with IPE, IPEA, HEA and HB
Modules attachment	Bolts, Rivets, Clamps (frameless)
Piles per MW (550Wp module)	~273 piles/MW <sup>(2)</sup> (60 modules per row)
(670 Wp module)	~248 piles/MW <sup>(2)</sup> (54 modules per row)
Terrain adaptability	20% N-S, 10% E-W <sup>(3)</sup>
Wind and snow loads tolerance	Tailored to site requirement
Rear shading factor	1.27%

## STRUCTURE

Material	High Yield Strength Steel
Coating	HDG, Pregalvanized & ZM <sup>(4)</sup>

## ELECTRONIC CONTROLLER SPECIFICATIONS

Controller	Electronic board with microprocessor
Ingress protection marking	IP65
Tracking method	
Advanced wind control	Customizable
Anemometer	Cup / Ultrasonic
Night-time stow	Configurable
Communication with the	

Power supply	Grid connection / String powered / Self-po
--------------	--

## WARRANTY

- (1) C-Shape piles under request
- (2) Depending on layout
- (3) N-S: max 20%, for slopes higher than 10% consult with TrinaTracker  
E-W: max 10%, for slopes higher than 5% consult with TrinaTracker

(4) ZM Coating under request. Please contact